



扫一扫 科尼乐智能

搅拌行业整体解决方案
www.cone-le.com

科尼乐智能装备科技有限公司

Cone-le Intelligent Equipment Technology Co., LTD

地址 (Add) : 青岛市城阳区玉皇岭工业园

(Yuhuangling Industrial Park Chengyang Dist Qingdao City China)

邮编 (P.C.) : 266107

电话 (Tel) : 150-5325-7766

0532-87876998

传真 (Fax) : 0086-532-87876998

信箱 (E-mail) : sales@co-nele.ren

网址 (http) : <http://www.cone-le.com>

因本产品不断改进如有改动恕不另行通知

Production may change due to technical progress subject may be modified without notice



MIXING INDUSTRY
overall solution

Company profile 公司简介

科尼乐智能装备科技有限公司位于美丽的海滨城市--青岛, 国家科技创新企业, 最具专业化、最具实力的混合设备制造企业之一, 产品在多个行业, 多个领域广泛应用。科尼乐源于欧洲先进、严谨的技术理念, 时刻关注国内外业界的技术动向, 掌握和剖析同行产品的优缺点。在产学研方面积极开展, 与国内一类大学进行新材料、新工艺的深入合作研究, 注重科技成果的转化, 先后获得100余项国家专利, 其中包含多项发明专利。科尼乐产品一直以优异的品质应用于国内各省市并出口至欧洲、美洲、亚洲、非洲、大洋洲等80余国家及地区。

Co-nele Intelligent Equipment Technology Co., LTD is one of the national science & technology innovating enterprises located in Qingdao, a beautiful coastal city. The company is the most professional one and ranks in the top of the mixing equipments manufacturers with its products applied widely. Basing on the advanced European technology, We keep close eye to the state of the art and we know well about competitors and ourselves. We pay great attention to product research and development, and till now have gained over 100 national patents. CO-NELE provides high quality products throughout the country and also exports to more than 80 countries and regions from Europe, America, Asia, Africa and Australasia.

- | | |
|-------------------------------|--|
| 1. 国内同行业首家通过欧盟CE认证。 | 1.The first company who got CE certificate in the same industry in China. |
| 2. 混合搅拌设备研究院A级单位。 | 2.A-level unit of Mixing Machine Research Institute. |
| 3. 山东省著名商标、青岛市著名商标。 | 3.Shandong Famous brands. |
| 4. 设计、制造能力最强的行星混合设备企业。 | 4.The strongest design and manufacturing capability planetary mixer manufacturer. |
| 5. 质量、环境、健康安全三体系示范单位。 | 5.Obtained ISO9001, ISO14001, ISO45001 system certification. |
| 6. 知识产权管理体系认证。 | 6.Intellectual Property Management System Certification. |
| 7. 立轴行星式搅拌机国内市场占有率第一。 | 7.Planetary mixer has the first domestic market share. |
| 8. 行星式强力混合设备规格型最全的专业化厂家。 | 8.A fullest model range of planetary mixer manufacturer. |
| 9. 国内第一台全油浴润滑方式免维护的集成化行星式减速机。 | 9.With the First entirely oil-immersed gear box equipped in planetary type mixer in China. |
| 10. 中国最大的行星搅拌机生产基地。 | 10.The largest production base planetary mixer in China. |
| 11. 中国出口最多的行星搅拌设备企业。 | 11.The largest exporter of planetary mixer in China. |
| 12. 中国非标搅拌设备的设计研发制造中心。 | 12.China non-standard mixing equipment design research and manufacture center. |
| 13. 中国最具有自主知识产权的行星混合设备公司。 | 13.China's most independent intellectual property rights owner of the planetary mixer. |



Product introduction 产品介绍

CO-NELE搅拌机整体设计更加人性化, 所有零部件都安装在搅拌筒体上, 检修空间大, 便于整机安装及更新。
The design of CO-NELE mixer is much more humanize. All the spare parts installed on the barrel, which make the maintain space bigger. So it's convenient to install and renewal for the whole equipment.




Enterprise qualification/Patent certificates

企业资质证书/专利证书

CE ISO9000 国内同行业首家通过“CE”认证
The first CE certification in the same industry in China.




CS 高效双卧轴搅拌机 Twin-shaft mixer



1 轴端密封 Shaft sealing

机械密封 Mechanical seal


- 采用浮动油封环及特制的密封件与机械密封组成的迷宫式保压型密封结构,可阻止物料进入;
- 机械密封中设有耐磨保护环,可保证密封持续稳定,且使物料不靠近轴端,延长搅拌机使用寿命;
- 分体式组装,易于拆卸和更换。
- A labyrinth type pressure retaining seal structure composed of floating oil seal rings, specially designed seals, and mechanical seals can prevent materials from entering.
- There is wear protection board in the mechanical seal, It can ensure the sealing system enduring stable. The material is not close to the shaft head. Prolong the service life seal.
- Split assembly, easy to remove and replace.



气雾润滑自密封轴端

Air mist lubricated self - sealing shaft end

- 采用原装进口密封材料,使用寿命长;
- 采用多重密封结构,密封更可靠;
- 润滑油位报警语音提示功能;
- 实现无人值守运行模式;
- 无黄油泵运行成本更低。
- Adopt original imported sealing material, long service life.
- Adopt multiple seal structure, seal more reliable.
- Oil level alarm.
- Realize unattended operation mode
- Running cost is lower without the oil pump



2 搅拌装置 Mixing tool

标准搅拌装置 Standard

- 采用专利设计的搅拌装置,搅拌物料匀质性高;
- 搅拌臂流线型铸造,搅拌阻力小,抱轴机率低;
- Using patent design of mixing device can get high material homogeneity;
- Streamline arms, mixing resistance is small, less likely to hold shaft;






双螺带搅拌装置 Twin-spiral (专利 patent)

- 搅拌叶片螺旋带布置, 效率提高15%, 节能15%, 物料搅拌匀质性超高;
- 采用大螺距设计理念, 降低运转阻力, 减少积料, 抱轴率低。
- The spiral blade can increase the mixing efficiency 15%, energy saving 15%, mix material more homogeneous.
- Reduce the running resistance, low holding shaft rate.



大骨料搅拌装置 Large aggregate mixing device

- 用于大骨料搅拌, 最大可适用160mm的骨料;
- 主要用于水工和废物处理行业。
- Maximum aggregate can be 160 mm;
- Mainly used in hydraulic industries and waste treatment industries.



3 轴端润滑 Shaft seal lubrication

全自动油脂润滑 Automatic grease lubrication

- 专供的四泵芯油泵, 独立供油, 维护检修方便;
- 输出高压油脂, 粘度大且密封可靠, 同时耗油量小, 可有效减少油脂对物料污染。
- Four cores grease pump. Independent oil supply. Easy to maintenance. output high pressure grease. High viscosity grease. small grease consumption.
- Can effectively reduce the oil pollution for the material.




全自动气雾润滑 Automatic air mist lubrication

- 采用压缩空气雾化润滑, 润滑效果好;
- 轴端独立气压检测及语音提示功能;
- 环保节能, 润滑介质对物料零排放, 无污染。
- Lubrication oi atomized by the compressed air, It makes lubrication effect very good.
- Independent air pressure detection and voice prompt function at shaft end.
- No lubrication oil goes into material. No pollution to the environmental with zero-emission.



4 搅拌轴轴承 Shaft Bearing (专利 patent)

- 主轴轴承与轴端密封分离式设计, 当轴端密封损坏时, 不会影响到轴承的正常工作;
- 此设计便于轴端密封拆卸更换。
- Shaft bearing and sealing are separate. Can protect the bearing when the sealing is broken.
- Easy to replace.



5 传动装置 Gearbox

- 采用厂家专供的行星减速机, 传动平稳, 噪声低, 使用寿命长, 无漏油。
- Stable transmission, low noise, long service life, no oil leakage



6 皮带自张紧装置 Belt self-tensioning device (专利 patent)


- 可避免皮带非正常磨损、损坏;
- 可降低维护人员的劳动强度, 并减少维护成本。
- Avoid belt abnormal wear and damage.
- Reduce maintenance costs.



7 卸料装置 Discharge door

偏心式卸料门 Eccentric discharge door



- 偏心式卸料门, 模块化设计, 密封可靠, 磨损小;
- 触点式感应开关, 耐用、可靠。
- Eccentric discharge door, modular design, reliable sealing, wear small.
- Durable and reliable limit switch.





大尺寸卸料门 Large size discharge door

- 大开口设计,用于快速卸料需要。
- 液压驱动,卸料门开关可靠。
- 带有开关门信号检测装置,控制更方便。
- 无死角搅拌,搅拌过程无花料、干料,搅拌更均匀。
- 尤其使用于高性能混凝土、干硬性混凝土
- 卸料门配置耐磨衬板,使用寿命长。
- 双卸料门设计,使用于PC行业多点卸料生产模式。
- Large opening design for quick discharge.
- Hydraulic drive, open and close more reliable.
- With the signal of position of the door, control facility.
- Without dead angle discharge structure, more uniform mixing.
- Especially suit the UHPC and dry concrete.
- With wear-resisting liner, long service life.
- Double discharge door, suit product the PC concrete



8 液压站防护罩 (选配) Hydraulic system protect cover (Option)

- 全面保护液压和润滑系统,使用更放心。
- 带有气弹簧开启装置,开启省力。
- 带有透明观察视窗,可视性好。
- Protect the hydraulic and lubricate system, feel free to use.
- With air spring equipment, easy open and close.
- With transparent glass window, best visibility.



9 人性化设计 Humanization design

- 双层踏步,符合人体结构的踏步高度。
- 带有维护爬梯,进出搅拌机安全方便。
- 带有活动尼龙盖板,防止检修门粘料。
- Double step, conform to the ergonomics.
- With maintenance ladder, facility to access mixer.
- With the nylon cover on the maintenance port, prevent sticky concrete.



10 智能物联网 (选配) Intelligent Internet (Option)

- 维护保养提示;
- 故障报警装置;
- GPS定位、微信推送功能。
- Maintenance tips.
- Fault alarm.
- GPS positioning, Wechat push.



| 型号 Type | CHS750 | CHS1000 | CHS1250 | CHS1500 | CHS2000 | CHS2500 | CHS3000 | CHS3500 | CHS4000 | CHS4500 | CHS5000 | CHS6000 |
|-------------------------------|--------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|
| 进料容量(L) Input capacity | 1125 | 1500 | 1875 | 2250 | 3000 | 3750 | 4500 | 5250 | 6000 | 6750 | 7500 | 9000 |
| 出料容量(L) Output capacity | 750 | 1000 | 1250 | 1500 | 2000 | 2500 | 3000 | 3500 | 4000 | 4500 | 5000 | 6000 |
| 搅拌机功率(KW) Mixer power | 30 | 37 | 22×2 | 30×2 | 37×2 | 45×2 | 55×2 | 55×2 | 75×2 | 75×2 | 45×4 | 55×4 |
| 泵站电机功率(KW) Hydraulic power | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 4 | 4 |
| 搅拌臂个数(个) Paddles number | 2*4 | 2*5 | 2*5 | 2*6 | 2*6 | 2*7 | 2*8 | 2*9 | 2*9 | 2*10 | 2*11 | 2*12 |
| 重量(Kg) Weight | 4200 | 4700 | 5000 | 5400 | 7800 | 8300 | 8900 | 9500 | 12000 | 14000 | 16000 | 18000 |
| 外形尺寸 (mm) Dimension | 2800 | 3000 | 3000 | 3200 | 3400 | 3640 | 3880 | 4100 | 4200 | 4480 | 4760 | 5040 |
| | 2180 | 2180 | 2180 | 2180 | 2600 | 2600 | 2600 | 2600 | 2950 | 2950 | 2950 | 2950 |
| | 1970 | 1970 | 1970 | 1970 | 2265 | 2265 | 2265 | 2265 | 2450 | 2450 | 2450 | 2450 |



CSW 双轴混合机 Double shaft mixer



1 传动装置 Drive device

- 采用厂家专供的行星减速机, 传动平稳, 噪声低, 使用寿命长, 无漏油。
- Use the planetary gearbox, smooth transmission, low noise, long service life, no oil leakage.



2 皮带自张紧装置 Belt self-tensioning device (专利 patent)

- 可避免皮带非正常磨损、损坏;
- 可降低维护人员的劳动强度, 并减少维护成本。
- Can avoid belt abnormal wear and damage;
- Can reduce the labor intensity of maintenance personnel, and to reduce maintenance costs.




3 搅拌装置 Mixing device

- 双搅拌轴设计, 搅拌臂采用快速可拆装结构, 易于维修和更换。
- 螺旋线布置的搅拌臂加刀片式结构的搅拌刀, 有效提升物料匀质性。
- Twin-shaft design, Mixing arm structure easy to tear open outfit, easy to repair and replacement.
- Helix arrangement of stirring arm stir in the structure of the blade knife, effectively improve the material qualitative. Easy cleaning to all internal parts of the Mixer.



4 卸料装置 Discharge door

- 卸料门采用专利技术的双开门设计, 双气缸驱动, 全密封结构, 无漏料, 卸料门可拆卸更换, 易于维护。
- Discharging door adopts the patent technology of double door design, dual cylinder to drive, fully sealed structure, no leakage, removable replacement discharging door, easy to maintain.



5 气控箱 Air control case

- 气路元件集中安置, 安全、便捷、美观。
- Gas path components placed centrally, safe, convenient and beautiful.





6 飞刀装置 (选配) Coultter device (Option) (专利 patent)

- 采用专利技术的超紧凑结构飞刀装置,设计双层密封圈,搭配耐磨合金飞刀,配合主搅拌刀运转可使物料迅速混合均匀,同时可有效分散纤维和抱团的物料。
- Fly knife device adopts the patent technology of ultra compact structure, double seal design, collocation of wear-resistant alloy, cooperate with the stirring knife operation can make rapid mixing material, at the same time can effectively disperse fibre materials and other means.



7 在线取样器 (选配) Working sampling device (Option)

- 采用气动装置的取样器,可以对搅拌物料进行实时抽样检验,从而确定最佳混合时间,保证搅拌质量。
- Sampler adopts pneumatic device, the mixing materials can be real-time sampling inspection, to determine the optimal mixing time, ensure the quality of mixing.



| 型号 Type | CSW2000 | CSW3000 | CSW4000 | CSW6000 | CSW8000 | CSW10000 | CSW12000 | CSW15000 |
|------------------------------|----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|
| 总容量 (L) Total capacity | 2000 | 3000 | 4000 | 6000 | 8000 | 10000 | 12000 | 15000 |
| 工作容量 (L) Working capacity | 800~1200 | 1200~1800 | 1600~2400 | 2400~3600 | 3200~4800 | 4000~6000 | 4800~7200 | 6000~9000 |
| 装载重量(Kg) Load weight(Kg) | 800~1200 | 1200~1800 | 1600~2400 | 2400~3600 | 3200~4800 | 4000~6000 | 4800~7200 | 6000~9000 |
| 电机功率 (KW) Mixing Power | 11×2 | 15×2 | 22×2 | 30×2 | 37×2 | 45×2 | 55×2 | 75×2 |
| 总重量 (KG) Weight | 2800 | 3600 | 4000 | 6100 | 7400 | 8000 | 9100 | 11000 |

CDW 单轴混合机 One shaft mixer



- 结合德国先进技术自主研发的高效混合机,高效率混合搅拌;
- 配合其辅助高速飞刀装置,能快速打散抱团及特殊物料;
- 具有耐磨材质制成的搅拌臂、搅拌叶片及筒体,延长其使用寿命;
- 大开口卸料门设计,配合硅质软性密封材料,无泄漏,卸料快;
- 此种机型可广泛用于建材、特种砂浆、墙面涂料、陶瓷等行业;

- The one shaft dry mixer adopts German advanced technology can mix materials efficiently.
- The fly cutter device can quickly break up clumps and special materials.
- Mixing arm, mixing blade and tank made of wear-resistant material to prolong its service life. Pneumatic large discharging door with silicon soft sealing material can quickly.
- Large opening discharge door design, with silicon soft sealing material to ensure discharge quickly and no leakage.
- One shaft dry mixer is widely used in building materials, special mortar, wall paint, ceramics and other industries.



| 型号 Type | CDW800 | CDW1200 | CDW1600 | CDW2000 | CDW3000 | CDW4000 | CDW6000 | CDW8000 |
|---|---------|---------|---------|----------|-----------|-----------|-----------|-----------|
| 总容量 (L) Total capacity | 800 | 1200 | 1600 | 2000 | 3000 | 4000 | 6000 | 8000 |
| 工作容量 (L) Working capacity | 320~640 | 480~720 | 640~960 | 800~1200 | 1200~1800 | 1600~2400 | 2400~3600 | 3200~4800 |
| 装载重量(Kg) Load weight(Kg) | 320~640 | 480~720 | 640~960 | 800~1200 | 1200~1800 | 1600~2400 | 2400~3600 | 3200~4800 |
| 电机功率 (KW) Mixing Power | 15 | 22 | 30 | 37 | 55 | 75 | 55×2 | 75×2 |
| 电机功率 (KW) Coultter device Mixing power(Kw) | 4×2 | 4×2 | 4×2 | 4×2 | 4×3 | 4×3 | 4×4 | 4×4 |
| 总重量 (KG) Weight | 1500 | 1900 | 2100 | 2300 | 3000 | 3900 | 5400 | 6400 |



CLS 连续式搅拌机

Continuous mixer



- 具有自主研发的高匀质性、高效率混合搅拌；
- 采用厂家专供行星齿轮减速机, 传动平稳可靠, 寿命长；
- 采用专利技术的皮带自张紧装置, 可有效避免皮带非正常磨损和损坏；
- 采用耐磨合金铸铁的搅拌叶片和衬板, 能有效保证设备使用寿命；
- 可广泛用于路基材料、污泥、尾矿石等行业。
- The self-developed mixing device ensures uniform and efficient mixing materials.
- Planetary reducer ensures smooth and reliable transmission and prolongs service life.
- The belt self-tensioning device with patented technology can effectively avoid abnormal wear and damage of the belt.
- Mixing blade and plate are made in wear-resistant alloy cast iron can effectively ensure the service life of the equipment.
- Continuous mixer is widely used in roadbed materials, sludge, tailings and other industries.



| 型号 Type | CLS05015 | CLS06025 | CLS07035 | CLS08050 | CLS09075 | CLS10090 | CLS11110 |
|-----------------------------------|----------|----------|----------|----------|----------|----------|----------|
| 项目 Item | | | | | | | |
| 输送量(th) Conveying capacity(th) | 50~150 | 100~250 | 150~350 | 250~500 | 350~750 | 500~900 | 650~1100 |
| 搅拌长度(mm) Mixing section(mm) | 2600 | 2800 | 3200 | 3600 | 4000 | 4400 | 4800 |
| 电机功率(Kw) Mixing power(Kw) | 11×2 | 15×2 | 22×2 | 30×2 | 45×2 | 55×2 | 75×2 |
| 重量(Kg) Weight(Kg) | 4100 | 5000 | 6200 | 7900 | 8500 | 9800 | 11000 |

AMS 沥青搅拌机

Asphalt mixer



- 适用于各种热拌、温拌及再生沥青混凝土搅拌要求。
- 采用大尺寸翻转式卸料门, 采用气缸驱动搅拌无死角, 卸料速度快。
- 卸料门处布置有加热保温系统, 有效避免卸料门粘料问题。
- 搅拌刮刀及衬板采用高铬耐磨合金, 具有极强的耐磨性。
- 特殊耐高温轴端密封设计, 并配自动润滑系统, 使用寿命长, 无需人工维护。
- 采用硬齿面工业减速机及开式同步齿轮设计, 搅拌机罐体采用分体式设计, 设计合理, 更便于搅拌机的维修维护。
- Suitable for all kinds of hot mix, warm mix and recycled asphalt concrete mixing requirements.
- Using large size flip unloading door, using cylinder driven mixing no dead angle, fast unloading speed.
- Angle, fast unloading speed.
- The unloading door is equipped with a heating and insulation system to effectively avoid the problem of adhesive material on the unloading door.
- Mixing scraper and lining plate are made of high chromium wear-resisting alloy, with strong wear resistance.
- Special high temperature resistant shaft end seal design, and equipped with automatic lubrication system, long service life, no manual maintenance.
- Adopt hard tooth surface, industrial reducer and open synchronous gear design, the mixer tank adopts split design, which is easier to maintain the mixer



| 型号 Type | AMS1000 | AMS1200 | AMS1500 | AMS2000 | AMS2500 | AMS3000 | AMS4000 |
|--------------------------------|---------|---------|---------|---------|---------|---------|---------|
| 项目 Item | | | | | | | |
| 搅拌能力 (KG) Stirring capacity | 1000 | 1200 | 1500 | 2000 | 2500 | 3000 | 4000 |
| 电机功率 (KW) Mixing Power | 2×15 | 2×18.5 | 2×22 | 2×30 | 2×37 | 2×45 | 2×55 |
| 转速 (RPM) Rotating speed | 53 | 54 | 55 | 45 | 45 | 45 | 45 |
| 总重量 (T) Weight | 3.2 | 3.8 | 4.1 | 6.8 | 7.5 | 8.2 | 9.5 |

CSS 双卧轴实验机 Twin shaft laboratorial mixer



- 占地体积小, 便于移动和安置;
- 搅拌装置设计独特, 安装拆卸快捷快速;
- 轴端密封采用浮动油封环及机械密封组成的整体式迷宫密封结构, 不仅工作可靠、寿命长, 同时易于拆卸和更换;
- 具有变频控制系统, 操作直观, 实验所得数据准确可靠;
- 配置丰富, 同时带有气动和手动卸料功能。
- Small footprint, easy to move and resettlement.
- The agitator design is unique can install and disassemble easily and quickly.
- The shaft sealing is composed of floating oil seal ring and mechanical seal ensure reliable work, longer service life, and easy to disassemble and replace.
- Frequency conversion control system, intuitive operation, accurate and reliable experimental data.
- Rich configuration, with pneumatic and manual discharge functions.



| 型号 Model | 出料容量 L Output | 进料容量 L Input | 出料质量 KG Output | 搅拌功率 kW Mixing power | 搅拌叶片 Mixer blade |
|-------------|------------------|-----------------|-------------------|-------------------------|---------------------|
| CSS60 | 60 | 90 | 144 | 4 | 5*2 |
| CSS90 | 90 | 130 | 216 | 5.5 | 6*2 |
| CSS150 | 150 | 225 | 360 | 7.5 | 6*2 |

CDW 单轴实验机 One shaft laboratorial mixer



- 占地体积小, 便于移动和安置;
- 搅拌工具多样, 采用犁刀式搅拌装置设计, 搅拌阻力小, 匀质性高;
- 轴端密封使用纤维盘根作为密封介质, 密封可靠、寿命长, 易于拆卸和更换;
- 具有变频控制系统, 操作直观, 验所得数据准确可靠;
- 气动大开口卸料门, 配合硅质软性密封材料, 无泄漏, 迅速卸料;
- 可视观察门, 工作过程安全掌控。
- Small footprint, easy to move and resettlement.
- Different kinds of mixing paddles and plough type stirring device ensure low agitation resistance, high uniformity.
- The shaft sealing is made of fiber packing can improve sealing performance and service life. It can be removed and replaced easily.
- Frequency conversion control system, intuitive operation, accurate and reliable experimental data.
- Pneumatic large discharging door with silicon soft sealing material can quickly discharge materials and ensure leak-tightness.
- Visual observation gate can safely control during the working process.



| 型号 Model | 总容量 L Total capacity | 工作容量 L Working capacity | 工作质量 KG Working weight | 搅拌功率 kW Mixing power | 搅拌叶片 Mixing blade |
|-------------|-------------------------|----------------------------|---------------------------|-------------------------|----------------------|
| CDW100 | 100 | 40~60 | 60~90 | 3 | 5 |
| CDW200 | 200 | 80~120 | 80~120 | 4 | 6 |
| CDW300 | 300 | 120~180 | 120~180 | 5.5 | 6 |

CHPW 高压清洗机1200

CHPW1200-High pressure washer



- 原装进口柱塞泵, 超高压, 清洗迅速干净;
- 装有全自动反冲洗过滤器, 有效延长元件使用寿命;
- 具有无线遥控、清洗工位启停功能;
- 装有储水箱, 带有底水位保护功能;
- PLC+触摸屏设计, 畅享人机交互操控。
- Original imported plunger pump with super high pressure can clean quickly.
- Fully automatic backwash filter effectively extend the service life.
- Wireless remote control the start-stop function of cleaning station.
- Water storage tank with bottom water level protection function.
- PLC+ touch screen design can enjoy man-machine interactive control.



| 型号 Model | 功率 kW Power | 工作压力 MPa Working pressure | 流量 L/min Flux | 水箱容量 L Water tank capacity | 重量 KG Weight |
|-------------|----------------|------------------------------|------------------|-------------------------------|-----------------|
| CHPW1200 | 22 | 50 | 21 | 80 | 380 |
| CHPW1200A | 22 | 50 | 21 | / | 320 |

Services 服务系统

- 售前服务: Service before sales**


担当客户的参谋和助手, 让用户的每一份投资都获得丰厚的回报; Give advice to customer
设备型号的选择: Assist customer to choose the right model
根据客户的特殊要求, 设计制造产品; Fabricate according to customer's requirement
为客户培训技术人员; Train operators for customer
提供新、特、难等物料搅拌的技术咨询; Technology consulting support for special material mixing
拟定合适的技术方案。Supply a suitable technical proposal
- 售中服务: Service in sales**


代办运输; Transportation
产品的预验收; Inspection
向客户介绍科尼乐的服务体系。Introduce service system to customers
- 售后服务: Service after sales**

协助用户拟定首次施工方案; Assist customer make the construction scheme
设备安装调试; Machine install and test
现场排除故障, 快速主动; Site trouble clearing
提供技术交流的机会; Technical exchange
免费拨打热线Free hotline: 400-661-6566
- 增值服务: Value added service**


重点项目全过程、零距离的技术跟踪服务; Overall process follow-up service
设备定期巡检服务; Regular visit inspect
为客户提供专业的定期保养标准。Periodic maintenance standard made for customer

Service Promise 搅拌机服务承诺





Applications 行业应用



Cases 应用案例



